

SPECIFICATIONS



Input Voltage.....208-240VAC Single Phase
 Kilowatt Rating.....6.0
 Maximum Amperage.....28 AMPS
 Water Inlet.....3/8” NPT
 Steam Outlet.....1/2” NPT
 Electrical connection.....Hard wired

Maximum Room Size (cubic Feet).....84

SteamSuite Plus features:

- Simple Sized – no complicated “tax return” formulas
- Constant steam at a constant rate (no steam lags or bursts)
- Lifetime PVD plating technology on control and steam head.
- Five year “no questions asked” factory warranty
- Can be plumbed 50 feet from the shower enclosure without having to purchase a larger kW unit.
- Stainless Steel drain pan.
- Time & temperature control; all metal construction – not plated plastic.

Installation Notes:

Install this generator according to the supplied installation guide. Follow local plumbing and electrical codes. Unit must be accessible.

Generator is factory sized: L x W x H = Cubic Feet. Choose the appropriate generator. For every additional foot of ceiling height over 8 ft, use the next larger generator. Always round up when calculating the total cubic feet.



Product Specification:


The steam generator shall approximately be 18.5” x 8.0” x 13.0” in dimension. The generator tank shall be made from stainless steel and include a Time and Temperature controller 4.25: x 2.5” x ¾”, and a Deluxe Steam head 2.5”Dia x 2”.

Shipping Information:

Weight.....28 lbs.
 Length.....21 in.
 Width.....10.32 in.
 Height.....14 in.

**select desired finish and replace the XX with the code*

PC = Polished Chrome
 PB = Polished Brass
 SN = Satin Nickel
 ORB = Oil Rubbed Bronze



For any further assistance please contact ThermaSol at 800.776.0711 or sales@thermasol.com

Visit www.thermasol.com for a complete product definition