

## FIT - 223 Fitting Package

### For models:

AK12, AK14 / 3K8, 3K10, 3K12, 3K14 / AT12, AT14 / 3T8, 3T10, 3T12, 3T14  
AK4.5, AK6, AK7.5, AK9, AK11, AK14  
AX4.5, AX6, AX7.5, AX9, AX11, AX14

### This Package Contents:

- A. (1) 3/8" Brass Close Nipple
- B. (1) 3/8"F NPT x 1/2"M NPT Brass Reducer
- C. (1) 3/4" Brass Close Nipple
- D. (1) 1/2" x 2" Brass Nipple
- E. (2) 1/2"F NPT x 1/2"F NPT Brass Union
- F. (1) 1/2"C x 1/2"C Brass Water Supply Ball Valve
- G. (2) 3/4"F NPT x 3/4"F NPT Brass Union
- H. (2) 1/2"C x 1/2"M NPT Copper Adapter
- I. (4) 3/4"C x 3/4"M NPT Copper Adapter
- J. (1) Teflon Tape Roll

### Installation:

This package contains the appropriate fittings and valves to ensure a professional plumbing installation. As each steam generator installation and corresponding plumbing runs is unique, common 1/2" (steam and water) and 3/4" (drain and pop safety) copper tubing and fittings can be purchased from a local hardware source to complete your installation. This package provides the essential, copper and brass components necessary for a serviceable and fully removable steam generator installation.

Verify package contents (above) with **Image A**. Locate appropriate fittings in installation **Image B**. Install as detailed using provided Teflon tape on all threaded fittings. While installing fitting package, attempt to locate unions near generator for easy access.

Note: Please refer to the steam generator manufacturer's installation and operation manual for specific and complete generator installation instructions.

\* Drain Valve and Pop Safety Valve Supplied With Generator

