

STEAM GENERATOR CONTROL KIT

SPECIFICATION SHEET

MODEL: KT3 3-BUTTON DIGITAL CONTROL
FOR USE WITH AK STEAM GENERATOR

Features

- 3-button digital control with on/off temperature and time duration setting.
- Display alternates between ambient room temperature and time remaining.
- Features built-in sensor.

Installation

- Control mounts inside steam room only.
- Control housing to be mounted in 2 3/8" diameter hole in wall
- Temperature sensor mounts in 7/8" diameter hole located 6" down from 84" ceiling.
- Control and sensor cables connect to PCA inside steam generator.

INSTALLATION VIEW



KT3 Digital Control
3"H x 3"W x 1/2"D

			Item Number
Digital Steam Control Kit with control, sensor cables and ComfortFlo steam head.			
KT60-CP	Chrome		9114-131
KT60-PN	Polished Nickel		9114-135
KT60-BN	Brushed Nickel		9114-136
KT60-ORB	Oil Rubbed Bronze		9114-137
KT60-BB	Brushed Bronze		9114-138
KT60-MB	Matte Black		9114-139

Only one KT3 may be installed and it must be mounted in the steam room.

Not intended for use as installation instructions.
Refer to specific generator model installation instructions for further detail.



ComfortFlo Steam Head
2-3/4"H x 3"W x 1-7/16"D

AMEREC
525 E Cokato Street | Cokato, MN 55321
Toll-Free 1-800-331-0349
amerec@amerec.com | www.amerec.com

Amerec reserves the right to change specifications and design without notice.
© 2021 Amerec Steam

06/21

amerec[®]
STEAM. SAUNA. SOLUTIONS.